

## ShopSite Knowledgebase

### **When I Click on "Reports", I Get an Internal Server Error**

Product: ShopSite SC

Version: 4.X, 5.X

Platform: UNIX

In ShopSite, when a merchant clicks on "Reports", they see a Server Error. On the Netscape browser, they'll see:

This server has encountered an internal error which prevents it from fulfilling your request. The most likely cause is a

misconfiguration. Please ask the administrator to look for messages in the server's error log.

In IE, you'll see the "HTTP 500 - Internal server error".

The link is stathandler.cgi, and URL is typically:

`http://cgi-bin/bo/stathandler.cgi`

Looking at the Web Server error logs shows this:

[Thu Feb 8 13:21:19 2001] [error] [client x.x.x.x] Premature end of script headers: /cgi-bin/bo/stathandler.cgi

The Server Error happens right away.

Solution ID: S04366

One thing to check is the contents of the data/ip subdirectory directory. Locate your data directory (Preferences->Hosting Service->Data Directory). In UNIX, go to this directory, and observe that there is an ip subdirectory.

Check if there is a core file in this directory. If so, type "file core". You may see something like this:

% file core

core: ELF 32-bit MSB core file SPARC Version 1, from 'stathandler-de

OR

% file core

core: ELF 32-bit LSB core file of 'stathandler-deb' (signal 11), Intel 80386, version 1

If this is the case, find the OLDEST ip\*.new file. Do this by "ls -lt istats\*.new". The oldest file will be the last file listed.

Look at the contents of this file, using cat:

% cat istats.1246.new

1 First Product

2 3.50

3 1

4 3.50

5

utwo-1

6 http://suppfront.openmarket.com:8888/4.3/umalitwo/page1.html

7 dhcp1-102.openmarket.com

8 16/Feb/2001

Each line in the istats\*.new file MUST begin with a number. In fact, each line has ascending numbers, and there should be data after each number, separated by a space. In the example above, line 5 only contains "5", and line 6 contains "utwo-1". Lines 5 and 6 likely have to be joined. In a UNIX editor, join these two lines, so that it now looks like this:

% cat istats.1246.new

1 First Product

2 3.50

3 1

4 3.50

5 utwo-1

6 http://suppfront.openmarket.com:8888/4.3/umalitwo/page1.html

7 dhcp1-102.openmarket.com

8 16/Feb/2001

Click on Reports again.

You should get past the Internal Server Error. If the error persists, examine the istats\*.new files in the manner above. They may be corrupted in a similar way.

telnet access will be required for technical support to examine this problem remotely.

<https://support.shopsite.com/KBase/questions/2398/>